

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E510939  
**Report Reference** E510939-2022-04-20  
**Date** 2022-April-22

**Issued to:** PFLITSCH GmbH & Co. KG  
Ernst-Pflitsch-Strasse 1  
Hueckeswegan 42499 DE

**This is to certify that  
representative samples of**

CABLE FITTINGS FOR USE IN ZONE CLASSIFIED  
HAZARDOUS LOCATIONS

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.


**Standard(s) for Safety:** See next page for standards.

**Additional Information:** See the UL Online Certifications Directory at  
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** E510939  
**Report Reference** E510939-2022-04-20  
**Date** 2022-April-22


This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Cable Fittings, Series LevelEx, LEx followed by 2 or 3, followed by 16, 20, 25, 32, 40, 50, 63, 012, 034, 038, 100, 114, 200 or 212, followed by ms or st, followed by HTS for use in Class I, Zone 1, AEx eb IIC Gb; Ex eb IIC Gb; Zone 20, AEx ta IIIC Da; Ex ta IIIC Da Hazardous Locations. For use with cable type TC-ER-HL tray cable with an overall jacket and a separate equipment grounding conductor. Thread sizes 1/2 to 2-1/2 in. NPT inclusive or M16 to M63 inclusive.

Cable Fittings, Series LevelEx, LEx followed by 2 or 3, followed by 16, 20, 25, 32, 40, 50, 63, 012, 034, 038, 100, 114, 200 or 212, followed by ms or st, followed by HTS for use in Class I, Zone 2, AEx ec IIC Gc; Ex ec IIC Gc; Zone 22, AEx tc IIIC Dc; Ex tc IIIC Dc Hazardous Locations. For use only with TC and TC-ER cable. Thread sizes 1/2 to 2-1/2 in. NPT inclusive or M16 to M63 inclusive.

## STANDARDS:

UL 2225, Cables and Cable-Fittings for Use in Hazardous (Classified) Locations  
CSA C22.2 No. 60079-0:19, Explosive atmospheres – Part 0: Equipment – General requirements  
CSA C22.2 No. 60079-7:16, Explosive atmospheres – Part 7: Equipment protection by increased safety “e”  
CSA C22.2 No. 60079-31:15, Explosive atmospheres – Part 31: Equipment dust ignition protection by enclosure “t”  
UL 514B, Conduit, tubing, and cable fittings  
CSA C22.2 NO. 18.3-12, Conduit, tubing and cable fittings  
UL 50E, Enclosures for electrical equipment, environmental considerations  
CSA C22.2 No. 94.2, Enclosures for electrical equipment, environmental considerations



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>