

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L216848-21-52102002-3
Report Reference E216848-20020125
Date 22-Jun-2021

Issued to: PFLITSCH GmbH & Co. KG
Ernst-Pflitsch-Strasse 1 Hueckeswagen
Germany 42499

This is to certify that
representative samples of QCRV2 - Outlet Bushings and Fittings - Component
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 514B, 6th Ed., Issue Date: 2012-07-13, Revision Date: 2020-05-22

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L216848-21-52102002-3
Report Reference E216848-20020125
Date 22-Jun-2021

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
1249(a) 7, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
1250(a) 8, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
1250(a) 9, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
1650(a) 7, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
1650(a) 8, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
1650(a) 9, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
1651(a) 11, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
1652(a) 13, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2051(a) 11, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2051(a) 7, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2051(a) 8, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2051(a) 9, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2052(a) 11, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings

B. Mahlen

Bruce Mahlenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L216848-21-52102002-3
 Report Reference E216848-20020125
 Date 22-Jun-2021

2052(a)13, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2052(a)7, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2052(a)8, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2052(a)9, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2053(a)16, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2054(a)18, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2054(a)20, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2553(a)11, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2553(a)13, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2553(a)16, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2553(a)7, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2553(a)8, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2553(a)9, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2554(a)18, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2554(a)20, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings

B. Mahrenholz

Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L216848-21-52102002-3
Report Reference E216848-20020125
Date 22-Jun-2021

3245(a)13, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3254(a)11, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3254(a)16, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3254(a)18, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3254(a)20, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3255(a)25, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3255(a)28, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3256(a)32, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3256(a)34, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3256(a)36, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
4055(a)16, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
4055(a)18, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
4055(a)20, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
4055(a)25, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
4055(a)28, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings

B. Mahrenholz

Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutus/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L216848-21-52102002-3
Report Reference E216848-20020125
Date 22-Jun-2021

4056(a)32, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
4056(a)34, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
4056(a)36, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
5056(a)32, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
5056(a)34, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
5056(a)36, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
5057(a)40, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
6358(a)44, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L216848-21-52102002-2
Report Reference E216848-20020125
Date 22-Jun-2021

Issued to: PFLITSCH GmbH & Co. KG
Ernst-Pflitsch-Strasse 1 Hueckeswagen
Germany 42499

This is to certify that
representative samples of QCRV8 - Outlet Bushings and Fittings Certified for Canada
- Component
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the
component requirements in the Standard(s) indicated on
this Certificate. UL Recognized components are incomplete
in certain constructional features or restricted in
performance capabilities and are intended for installation in
complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: CSA C22.2 NO. 18.3-12, 2nd Ed., Issue Date: 2012-07-01,
Revision Date: 2020-05-22

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark.
Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified
and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L216848-21-52102002-2
Report Reference E216848-20020125
Date 22-Jun-2021

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
1249(a) 7, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
1250(a) 8, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
1250(a) 9, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
1650(a) 7, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
1650(a) 8, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
1650(a) 9, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
1651(a) 11, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
1652(a) 13, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2051(a) 11, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2051(a) 7, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2051(a) 8, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2051(a) 9, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2052(a) 11, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings

Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L216848-21-52102002-2
 Report Reference E216848-20020125
 Date 22-Jun-2021

2052(a)13, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2052(a)7, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2052(a)8, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2052(a)9, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2053(a)16, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2054(a)18, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2054(a)20, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2553(a)11, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2553(a)13, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2553(a)16, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2553(a)7, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2553(a)8, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2553(a)9, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2554(a)18, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
2554(a)20, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings

B. Mahlenz

Bruce Mahlenz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutus/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L216848-21-52102002-2
 Report Reference E216848-20020125
 Date 22-Jun-2021

3245(a)13, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3254(a)11, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3254(a)16, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3254(a)18, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3254(a)20, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3255(a)25, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3255(a)28, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3256(a)32, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3256(a)34, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
3256(a)36, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
4055(a)16, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
4055(a)18, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
4055(a)20, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
4055(a)25, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
4055(a)28, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings

B. Mahrenholz

Bruce Mahrenholz, Director North American Certification Program

UL LLC




Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L216848-21-52102002-2
Report Reference E216848-20020125
Date 22-Jun-2021

4056(a)32, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
4056(a)34, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
4056(a)36, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
5056(a)32, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
5056(a)34, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
5056(a)36, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
5057(a)40, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings
6358(a)44, Prefixed by 1, 2, 3, or 8. (a) can be dp, LF, LFp, stp, ep, LFep, step. Suffixes by /RU, may be followed by S and/or V4A.	Outlet Bushings and Fittings



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>