

PFLITSCH Machines

MultiCut enquiry form

Contact details

 Customer number

 Customer address

 Customer name

 Date

 Filled out by

Machine

MultiCut HH + SK XXXXX

Scope of delivery: Basic machine with customised cutting contours, incl. lever; incl. suitable infeed aid.

MultiCut MS HYD + SK XXXXX

Scope of delivery: Basic machine with customised cutting contours, version incl. conversion kit for MS HYD S; drive, incl. suitable infeed aid.

MultiCut EH AM + SK XXXXX

Scope of delivery: Basic machine with customised cutting contours, version incl. conversion kit for EH AM2 60 KN; drive, incl. suitable infeed aid. *This combination is only approved for machining steel zinc-plated cable trunking.*

Alternative drives

Manual hydraulic drive

EH AM2 60 KN

Hydraulic unit, mains-operated

MS HYD S

Cutting contour

The cutting plate can be customised by combining different sizes of the cutting contours for different trunking profiles. Because there are different variants of trunking contour, all contours you would like to use for a customised solution must be checked first to make sure that they can be accommodated. This is taken care of by PFLITSCH.

Material

Hot-dip galvanised steel

AISI 304 stainless steel

PIK-Trunking

PIK 15/15	PIK 60/60	PIK 150/60
PIK 30/30	PIK 80/60	PIK 200/60
PIK 40/40	PIK 100/60	PIK TL 60
PIK 60/40	PIK 120/60	

Industrial-Trunking

KD 50/50	TL 75
KD 75/75	TL100
KD 100/100	
TL 50	

Accessories

Analogue length stop for MultiCut, length: 1,000 mm

MultiCut LA

Digital length stop for MultiCut, length: 1,000 mm

MultiCut DLA